

SEALER CIMENTART

TECHNICAL DATA SHEET

CIMENTART®
MICROCEMENT

Acrylic sealer for cement,
concrete and wood surfaces

Increased cohesion
over any porous surface

Enhances the aesthetic
finish of cement, concrete
and microcement surfaces

Assists to the application
of the bi-component
polyurethane varnish

Interior and exterior



INNOVATE SME

Valid until Nov 16th 2020



Commitment with the environment

CimentArt Microcement S.L.
Teléf: +34 965 654 637

Avda. Carrer la Mar, 12 - CP: 03560
www.grupocimentart.com

El Campello (Alicante)
info@grupocimentart.com



CIMENTART SEALER – TECHNICAL DATA SHEET

CIMENTART SEALER is a coating ready to use whose formula is based on acrylic resins and water-repellent additives and is water-based, which makes it perfect for the consolidation and sealing of the Microcement coatings.

Its main characteristics are:

- Complete waterproofing of the surface.
- It allows the respiration of the surface.
- It enhances the aesthetical finishing and the marble effects of the Microcement.
- It makes easier the application of the **CIMENTART BI-COMPONENT POLYURETHANE**.

TECHNICAL DATA

<i>Emulsion of reactive silicates water-repellent</i>	
Finishing	Transparent
Color	Uncolored
Density	1.35 +- 0,02 Kg/L
Temperature of application	+ 5° °C / + 35°C
Solids content	60% ± 2%
Drying time	3 hours aprox.
Time to complete waterproofing	7 days
Shipping	Material not dangerous
Storing	Material not dangerous

USE INSTRUCTIONS

Once finished completely the application of any of the **CIMENTART Products** (Microcement, Fine, Nature, Solid Color or any of the iCem products), and the sanding and cleaning processes are complete on them, you would start applying the **CIMENTART SEALER**. It can also be applied in any cement or stamped concrete surface.

Apply directly with a varnish roller, a brush or an airless system, in an orderly way, a good layer without leaving excesses.

CIMENTART SEALER – TECHNICAL DATA SHEET

It should be applied over a clean, dry and dust-free surface.

The product is presented ready to use. We do not advise to dilute it.

Clean all tools with water.

EFFICIENCY

With 1 liter of CIMENTART SEALER you can cover 7-10 m² of surface, depending on the porosity of the surface itself. We recommend 1 layer for surfaces with no contact with water and 2 layers for surfaces with contact with water, like: shower plates, kitchen worktops and WC areas, exteriors surfaces, etc.)

PRESENTATION

- Recipients of 1 kg, 5 kg and 25 kg.
- Big container of 1000 kg.

STORING

12 months, in a dry place protected from bad weather in its original recipient hermetically closed.

CIMENTART MICROCEMENT SL. Our systems are based in the research done at our laboratories and the many years of practical experience we have.

We guarantee that our products are manufactured, packaged and labeled under the rules of Normative ISO 9001:2008.

We decline any responsibility if the end result is affected by external factors not under our control.

The end user must check that the product supplied is adequate to the needs that is going to be used for, doing a test in any case that must be necessary.

Review date: 08-08-18.

The present document cancels the earlier editions.

