

PRIMER PLUS

TECHNICAL DATA SHEET

Adherence promoter for surfaces with low absorption rate

Increased adherence over any type of surface

Ideal to create a strong adhesion in cement products

Interior and exterior

CIMENTART®
MICROCEMENT



INNOVATE SME

Valid until Nov 16th 2020



Commitment with the environment

CimentArt Microcement S.L.
Teléf: +34 965 654 637

Avda. Carrer la Mar, 12 - CP: 03560
www.grupocimentart.com

El Campello (Alicante)
info@grupocimentart.com



CIMENTART PRIMER PLUS – TECHNICAL SHEET

The **CIMENTART PRIMER PLUS** is a synthetic liquid made of acrylic copolymers that is used to enhance the adherence of the **CimentArt Microcemento and micro-mortars** to the surfaces where they are applied. In this case, the PLUS version is for surface with low absorption rate like (tiles, wood, porcelains, marble, etc.)

With the application of the **CIMENTART PRIMARY PLUS**, you achieve:

- A better adherence over any kind of surface.
- An increased cohesion of the surface.
- An increased impermeability.
- An increased durability.
- An increased resistance to cracks.
- An increased resistance to a possible alkaline Ph of surface.
- Durability of residual Tack (glue factor) of several weeks.

TECHNICAL DATA

Type	Acrylic copolymer
Aspect	Milky liquid
Color	White. When dry is transparent
Density	1,10 Kg/l ± 2%
Solids Content	58% ± 2%
Chlorides	Exempt
Shipping	Material not dangerous
Storing	Material not dangerous

CIMENTART PRIMER PLUS – TECHNICAL SHEET

USE INSTRUCTIONS

Apply directly over the surface, avoiding spilling the product, in a uniform way, without soaking.

Once applied the product, let it dry for a period of 30 minutes or till it is dry when you touch it.

It is applied using a brush or a varnish roller or even with an airless system.

In degraded surfaces repair the affected area and if needed apply a second layer and reinforce using the **CIMENTART Fiber Glass Mesh**.

Clean tools with water.

EFFICIENCY

The efficiency of 1 kg **CIMENTART Primer Plus**: 10 to 14 m², depending of the porosity and grade of absorption of the surface.

- 5 to 7 m² on high absorption surfaces.
- 10 to 15 m², on low absorption surfaces.

PRESENTATION

Is presented in recipients of 1 kg, 5 kg, and 25 kg.

STORING

12 months, in a dry place protected from bad weather in its original recipient hermetically closed.

CIMENTART MICROCEMENT SL. Our systems are based in the research done at our laboratories and the many years of practical experience we have.

We guarantee that our products are manufactured, packaged and labeled under the rules of Normative ISO 9001:2008.

We decline any responsibility if the end result is affected by external factors not under our control.

The end user must check that the product supplied is adequate to the needs that is going to be used for, doing a test in any case that must be necessary.

Review date: 12-09-18.

The present document cancels the earlier editions.

