

CIMENTWAX CIMENTART

CIMENTWAX CIMENTART

TECHNICAL SHEET

Crystallizer and brightener, based on wax for stuccos.

Fast application with a trowel or cloth.

Ideal to polish all kind of stucco coverings.

Product ready to use, user-friendly.

Easy to polish and to make a shining and mirror effect with a polishing machine.

CIMENTART®
MICROCEMENT



PYME INNOVADORA

Válido hasta el 21 de julio de 2025



Commitment to the environment

CIMENTWAX CIMENTART

With the use of **CIMENTWAX CIMENTART** you can crystalize, vitrify and brightening and the same time with only one product and its **STUCCO CIMENTART** coverings.

TECHNICA DATA

Presentation	White paste
Viscosity	Pasty mass
Density	1,10 ± 0,2
Composition	Acrylic wax and resins
Smell	Typical
Application	Steel trowel or cloth.
Drying Time	1-2 hrs. at 20°C / 60% relative humidity
Coverage	1 kg / 15 a 20 m2 approx. / 0,1 mm of thickness
Application Temperature	+ 5° °C / + 35°C
Mixture Proportions	Product ready to be use
Tools cleaning	Water
Packaging format	Bins of 750 ml
Solvents	None
Flammable point	Non-flammable
Epoxy	None
Transportation	No-dangerous material
Storage	No-dangerous material

CIMENTWAX CIMENTART USE INSTRUCTIONS

The most important point about the stucco is a smooth, well-polished and shining finishing.

1. Sand the whole surface with a mesh sandpaper 180 and vacuum the dust.
2. Sand again the whole surface, now using mesh sandpaper 400 and vacuum the dust.
3. Polish the whole surface with a sponge polishing disc 2000.
4. Apply **CIMENTWAX CIMENTART** with a steel trowel or cloth in thin layers, leaving no excess. This layer should be very thin and should be as smooth as possible.
5. Immediately after applying **CIMENTWAX CIMENTART** and before it dries completely, polish the surface with a wool polishing disc, until a completely shiny and silky finish is achieved. Continue polishing until you get the finish you like. Do not stand for a long time in the same area while polishing with the wool polishing disc. Continue moving the polisher continuously, without stopping it in the same area.

CIMENTWAX CIMENTART

To obtain an even more shining effect you can repeat the procedure as you wish (the application of **CIMENTWAX CIMENTART** in the same fashion polishing the surface with a lamb wool polishing bonnet).

*Note: to obtain a complete waterproofing of the **STUCCO CIMENTART** in places that are exposed to water (as bathroom walls or facades) 2 layers of **CLEAR COAT CIMENTART** protective varnish must be applied on the walls. On this case don't use **CIMENTWAX CIMENTART**. Polish the whole wall with a sponge polishing disk 2000 and finalize with a lamb wool polishing bonnet to obtain a completely shining surface without applying **CIMENTWAX CIMENTART**.

COMPLETE WATERPROFING STUCCO CIMENTART

If you wish to have completely washable walls or using the stucco on the bathroom walls, facades or walls that receive water, to achieve a complete protection of the walls we recommend to apply 1 layer of protective varnish **CLEAR COAT CIMENTART** for walls 1, using a microfiber roller or a short haired roller, covering all the surface and making sure to achieve a completely smooth and without bubbles application.

Once the layer is dry (approximately 2 hrs.) apply a second layer of **CLEAR COAT CIMENTART** in the same fashion.

APPLICATION GUIDE STUCCO CIMENTART

	Primer	Stucco Base	Stucco Fino	CimentWax	Polish	Clear Coat
Cement or tile walls, indoors where there is no water contact.	✓	✓	✓	✓	✓	
Cement or tile walls, outdoors.	✓	✓	✓		✓	✓
Smooth walls indoors where there is not contact with water.	✓		✓	✓	✓	
Smooth walls outdoors.	✓		✓		✓	✓
Bathroom and areas exposed to water.	✓	✓	✓		✓	✓
Kitchens	✓	✓	✓		✓	✓
Offices, shops.	✓	✓	✓	✓	✓	

*Note: If the protective varnish is going to be applied do not use **CIMENTWAX CIMENTART**.

CIMENTWAX CIMENTART

WARNINGS

Make the polishing process with a polishing machine (never a sanding machine) also use a disc number 2000.

Make short and semi-circular movements with a polishing machine, in an evenly fashion, over the whole wall, using a maximum speed of 1500 rpm (never polish with a maximum speed).

The application **CIMENTWAX CIMENTART** must have a natural shining and a complete polishing of the walls, creating more protection over the **STUCCO CIMENTART**. Apply the **CIMENTWAX CIMENTART** in a really thin layer, with steel trowel or cloth. Make sure the cloth don't leave hair on the surface as this would stick on the **CIMENTWAX CIMENTART**.

Sand any excess of wax, drops or any excess of **CIMENTWAX CIMENTART** before the final polishing with a mesh sandpaper 1000.

The excess of **CIMENTWAX CIMENTART**, will make the wool polishing process difficult and a proper polishing would not be achieve, there could remain imperfections and small roughening's on the surface. If this happens, it is really easy to solve, sand the **CIMENTWAX CIMENTART** excess with a mesh sand paper 500-800 until these disappear and then polish the surface with the lamb wool polishing bonnet.

Make sure that none of the sand paper or polishing disks damage the **STUCCO CIMENTART** with scratches.

The surface would be as shinning as you use the lamb wool polishing bonnet through the surface.

On the corners were the polishing machine do not reach, make the polishing manually.

Do not use the product if there is any liability of cold weather or raining. Do not apply the product if the temperature is under 5°C or over 35°C.

Never leave the final layer incomplete continue until the termination without any stops, in this way you will avoid marks, joints etc. if the surface if to big the application must be done by several people at the same time.

Avoid hits and scratches on the finished walls of **STUCCO CIMENTART**.

CIMENTWAX CIMENTART

Once the application is completed, let it dry for 7 days before using any water on the surface or masking tapes. If you need to do a painting job next to the **STUCCO CIMENTART** surface you must wait 7 days before placing any tape of the surface.

The tools are cleaned with water.

These products are considered no dangerous for shipping. Water based, free of dissolvent, alcohols or flammable products.

Do not place this product where kids can reach them. Avoid the contact with the eyes and the skin by using the proper equipment. In the case of eye contact wash your eyes with abundant water and make a doctor consultation in the case of any complication.

COVERAGE

With 750 ml of **CIMENTWAX CIMENTART**, there would be a coverage of 15 m2 making layers of 0.1 mm.

PACKAGING FORMAT

Containers of 750 ml.

STORAGE

12 months, in a dry places protected from outdoor climate, the product been on the hermetically closed container.

CimentArt Microcement SL. Our systems are based on research carried out in our laboratories and years of practical experience.

We guarantee that our products are manufactured, packaged and labeled under the guidelines of the ISO 9001: 2008 standard.

We decline any responsibility if the final result is affected by factors beyond our control.

The end user must verify that the supplied product meets the needs for which it will be used, having to carry out a prior test in each case that is necessary.

Revision date: 27-02-21..

This edition of this technical sheet cancels the previous ones.



RESPONSIBLE CARE
El Compromiso de la Industria Química
con el Desarrollo Sostenible